


BROADBAND OPTICAL FIBERS



OPERATING SPECTRAL RANGE: 275-2100 NM



FEATURES

- Transmits light over broad range of wavelengths from UV to NIR
- Low loss over the entire operating spectral range
- Lower focal ratio degradation as compared to standard fibers
- Custom sizes, buffers, jackets available

FIBER PROPERTIES

- Silica core, doped silica clad
- Step index profile
- Numerical aperture: 0.22 ± 0.02
- Proof test: 70 kpsi
- Operating temperature: -190°C to 385°C
- Wide variety of core:clad ratios

PRODUCT CODE	CORE DIAMETER [μm] ± 2 %	CLAD DIAMETER [μm] ± 2 %	COATING DIAMETER [μm] ± 3 %	STANDARD BUFFER	NUMERICAL APERTURE ± 0.02
SUVIR100/120PI	100	120	140	POLYIMIDE	0.22
SUVIR100/140PI	100	140	170	POLYIMIDE	0.22
SUVIR200/220PI	200	220	240	POLYIMIDE	0.22
SUVIR200/240PI	200	240	280	POLYIMIDE	0.22
SUVIR300/330PI	300	330	370	POLYIMIDE	0.22
SUVIR400/440PI	400	440	480	POLYIMIDE	0.22
SUVIR400/480PI	400	480	520	POLYIMIDE	0.22
SUVIR500/550PI	500	550	590	POLYIMIDE	0.22
SUVIR600/660PI	600	660	710	POLYIMIDE	0.22

OPTIONAL NYLON OR TEFLON JACKET FOR POLYIMIDE COATED FIBERS AVAILABLE.

OTHER SPECIFICATIONS UPON REQUEST.



FiberTech Optica

info@fibertech-optica.com • www.fibertech-optica.com
519.745.2763 / 514.352.6666

© April 2011 FiberTech Optica Inc. All rights reserved. No reproduction is permitted without prior authorization.